

INLINE PROCESS DENSITY AND
VISCOSITY MONITORING



rheonics.com
+41 52 511 32 00
🇨🇭 Winterthur

info@rheonics.com
+1 832 998 0606
🇺🇸 Houston

Product Portfolio



SRV



SRD

Description

Process viscometer for Newtonian and non-Newtonian fluids. Wide viscosity range - monitor the complete process.

Single instrument for process density, viscosity and temperature measurement.

Fluid Measurements

Viscosity Range

3 to 10,000 cP

0.5 to 50,000 cP (available)

1 to 3,000 cP

wider range available

Viscosity Accuracy

5% of reading (standard)

1% & higher accuracy available

5% of reading (standard)

higher accuracy available

Density Range

-

0.4 - 1.5 g/cc

Density Accuracy

-

0.01 g/cc

0.001 g/cc & higher accuracy available

Reproducibility

Better than 1% of reading

Better than 1% of reading

Temperature (inbuilt)

Pt1000 (DIN EN 60751 class B)

Pt1000 (Class B)

Operational Environment

Process Fluid Temperature

-40 up to 200 °C

-40 up to 200 °C

Ambient Temperature

max 150 °C

max 150 °C

Pressure Range

up to 5,000 psi

up to 5,000 psi

Mechanical

Material (Wetted parts)

316L Stainless Steel

316L Stainless Steel

Diameter x Length

Ø35 x 140 mm

Ø35 x 140 mm

Process Connection

3/4" NPT

3/4" NPT

Flange & sanitary connections available

Flange & sanitary connections available

Ingress Protection

IP68

IP68

Electrical Connection

M12

M12

Application

Designed for easy installation in pipelines, tanks, and process lines.

- Process viscosity control of slurries, emulsions and other non-newtonian fluids
- Polymerization monitoring
- Coating and ink viscosity control
- Marine fuel viscosity control

- Drilling mud density and viscosity
- Newtonian and nonnewtonian fluids
- Pipeline and pumping - efficiency and leak detection
- Fuel consumption monitoring



rheonics

inline process
density and viscosity
monitoring



DVP

Simultaneous density, viscosity and temperature measurement at HPHT conditions.

0.2 to 300 cP

0.1 cP below 1 cP

5% of reading (standard)

higher accuracy available

0 – 1.5 g/cc

0.001 g/cc

higher accuracy available

Better than 1% of reading

Pt1000 (class AA)

-40 up to 200 °C

max 150 °C

up to 10,000 psi

Titanium Grade 5

Ø35 x 120 mm

1" NPT

Flange & sanitary connections available

IP68

M12

- Gas and liquid density
- High pressure processes
- Custody transfer - liquid, gas
- LNG density metering
- Not suitable for liquids with magnetic particles



DVM

Designed for reservoir fluid analysis. Simultaneous density and viscosity measurement at 30,000 psi & 200 °C.

0.2 to 300 cP

lower than 0.2 cP available

0.1 cP below 1 cP

5% of reading (standard)

higher accuracy available

0 – 1.5 g/cc

0.001 g/cc

higher accuracy available

Better than 1% of reading

Pt100 (Class AA)

-40 up to 200 °C

max 200 °C

up to 30,000 psi

Titanium Grade 5

44 x 55 x 75.3 mm

1/4" HP (9/16-18 UNF)

IP69

Fixed cable

- HPHT fluid analysis
- PVT viscosity & density
- EOR density & viscosity
- Core flow fluid measurements
- Lubricant viscosity monitoring

Electronics & Communication



SME-TRD

Analog output	4-20 mA (3 channel) Viscosity, Density, Temp.
Digital output	Modbus RTU (RS-485) Ethernet USB HART (optional)
Wireless output	Bluetooth LE 4.0 Wi-fi (optional) WirelessHART/ISO100 (optional)
Display (SME-TRD)	Multi-line LCD (max. 55°C)
Operational temp.	max. 55 °C
Power supply	24 V DC
SME-TR(D)	IP65/66
SME-DRM	IP40/50
Software	Data acquisition and service



SME-DRM



rheonics

inline process
density and viscosity
monitoring

INVENTED, DESIGNED, AND BUILT WITH SWISS PRECISION

Invented, designed and built by an ETH Zurich spin-off team with over 150 years of collective experience in resonant sensor technology. Rheonics proprietary technology is protected by a growing portfolio of US & international patents.

Precision built in Switzerland, each Rheonics fluid density and viscosity sensor is designed to match your application needs. Whether you need to measure density and viscosity downhole at 30,000 psi and 200 °C or monitor the viscosity of polymerization reactions, we have a solution for you.

Rheonics density and viscosity sensors are available in probe and flow through styles. All Rheonics products are designed to withstand the harshest process environments including high level of shock, vibrations, abrasives & corrosives.

30 YEARS OF DEVELOPING INNOVATIVE FLUID DENSITY & VISCOSITY MONITORING

- 1985 • Conceptual framework at ETH Zurich
- 1990 • First viscometer patented
- 1998 • Gated PLL technology patented
- 2003 • Process Viscometer developed
- 2010 • Developed HPHT D-V sensor
- 2012 • rheonics incorporated
- 2013 • HPHT Viscosity and Density Sensor for Oil and Gas (DVM)
- 2014 • Inline process Density & Viscosity Sensor (DVP)
- 2015 • Inline process Viscometer (SRV)
- 2016 • Inline process Density & Viscosity Meter (SRD)

Contact Information

www.rheonics.com
info@rheonics.com

rheonics Inc.

3 Sugar Creek Center Blvd, Ste 100
Sugar Land, TX 77478
United States of America
+1 832 998 0606

rheonics GmbH

Technoparkstr. 2
8406 Winterthur
Switzerland
+41 52 511 32 00

Represented by

